

HIGH PERFORMANCE
SOLAR MODULES

REC PEAK ENERGY (BLK) SERIES

The REC Peak Energy Series modules are the perfect choice for building solar systems that combine long lasting product quality with reliable power output.



**MORE POWER
PER M²**



**ROBUST AND
DURABLE DESIGN**



**ENERGY PAYBACK
TIME OF ONE YEAR**



**OPTIMIZED FOR ALL
SUNLIGHT CONDITIONS**




Solar Systems
Windmill Hill, Ashill, Ilminster
Somerset TA19 9LP

Tel: 01823 481329

Fax: 01823 481042

www.solarsystemslimited.co.uk

REC PEAK ENERGY (BLK) SERIES



14.8 EFFICIENCY
63 MONTHS WORKMANSHIP WARRANTY
25 YEAR POWER OUTPUT WARRANTY

ELECTRICAL DATA @ STC	REC220PE	REC225PE	REC230PE	REC235PE	REC240PE	REC245PE
	BLK	BLK	BLK	BLK	BLK	BLK
Maximum Power - P_{MAX} (Wp)	220	225	230	235	240	245
Watt Class Tolerance - P_{TOL} (W)	0/+5	0/+5	0/+5	0/+5	0/+5	0/+5
Maximum Power Voltage - V_{MPP} (V)	28.7	29.1	29.4	29.8	30.4	30.6
Maximum Power Current - I_{MPP} (A)	7.7	7.7	7.8	7.9	7.9	8.0
Open Circuit Voltage - V_{OC} (V)	36.6	36.8	37.1	37.4	37.7	38.0
Short Circuit Current - I_{SC} (A)	8.2	8.2	8.3	8.3	8.4	8.4
Module Efficiency (%)	13.3	13.6	13.9	14.2	14.5	14.8

Values at Standard Test Conditions STC (Air Mass AM1.5, Irradiance 1000 W/m², Cell temperature 25 °C)

GENERAL DATA	
Cell Type	60 REC PE multi-crystalline cells 3 strings of 20 cells - 3 by-pass diodes
Glass	High-transparency solar glass with antireflection surface treatment by Sunarc Technology
Back Sheet	Double layer highly resistant polyester
Frame	Black anodized aluminium
Cable	Radox 4mm ² smart cable, 0.90m +1.20m
Connectors	Radox 4mm ² twist locking connector

TEMPERATURE RATINGS (235 W RATED MODULE)	
Nominal Operating Cell Temperature (NOCT)	47.9 °C (±2 °C)
Temperature Coefficient of P_{MPP}	-0.46 %/°C
Temperature Coefficient of V_{OC}	-0.32 %/°C
Temperature Coefficient of I_{SC}	0.011 %/°C

MECHANICAL DATA	
Dimensions	1665 x 991 x 38 mm
Area	1.65 m ²
Weight	18 kg

CERTIFICATION

Certified according to UL1703, IEC 61215 and, IEC 61730

WARRANTY

10 years limited warranty of 90% power output
25 years limited warranty of 80% power output
63 months workmanship warranty

MAXIMUM RATINGS	
Operational Temperature	-40 ... +80 °C
Maximum System Voltage	1000V
Maximum Load	551 kg/m ² (5400 Pa)
Maximum Wind Speed	197 km/h (safety factor 3)
Max Series Fuse Rating	15A
Max Reverse Current	15A

Note! Specifications subject to change without notice.

REC is a leading vertically integrated player in the solar energy industry. REC is among the world's largest producers of polysilicon and wafers for solar applications, and a rapidly growing manufacturer of solar cells and modules. REC is also engaged in project development activities in selected PV segments. Founded in Norway, REC is an international solar company, employing more than 4,100 people worldwide. REC had revenues in excess of NOK 9 billion in 2009, approximately EUR 1 billion and approximately USD 1.4 billion.

